



# Acceleration Mechanical Shock Tester

-----the table size can be customized

Model		SS-5	<b>SS-10</b>	SS-25	SS-50	SS-100	SS-200	SS-400
Load Capacity (Kg)		5	<b>10</b>	25	50	100	200	400
Table Size (mm)		120x120	<b>200x200</b>	350x350	450x450	650x650	750x750	850x850
Pulse Acceleration (m/s <sup>2</sup> )	Half Sine Wave	150~15000	<b>150~15000</b>	150~15000	150~6000	150~6000	150~3500	150~1500
	Trapezoid Wave	300~1000	300~1000	300~1000	300~1000	300~1000	300~1000	300~500
	Sawtooth Wave	150~1000	150~1000	150~1000	150~1000	150~1000	150~1000	150~500
Pulse width	Half Sine Wave	0.5~18	0.6~18	0.8~25	1.5~30	1.5~30	2~30	6~30
	Trapezoid Wave	6~12	6~12	6~18	6~12	6~12	6~12	6~12
	Sawtooth Wave	6~18	6~18	6~18	6~18	6~18	6~18	6~18
Drive Mode	Mechanical drive						Hydraulic drive	
External Dimension WxHxD (mm)	800x2200 x900	800x2200 x900	850x2250 x950	1000x2600 x1300	1100x2700 x1400	1300x2700 x1600	1300 x2700x1650	
Weight (Kg)	600	700	900	2600	3300	4000	4500	
Hydraulic Oil	No #46 hydraulic oil							
Power	AC 380V 50/60HZ							



# ® AI SI LI (CHINA) TEST EQUIPMENT CO., LTD

Tel.:0086-769-23164266 Fax:0086-769-22851784 Website:www.ASLItesting.com

Company Add.:Building C,JinHui Industrial Park, LiXin town,East City district 523125,DongGuan City,China



Shock Absorber pad



Test Curve

