

Temperature Humidity Test Cabinet

-----the internal dimension can be customized

- Internal volume: 1000Liters
- Temperature range: -70°C~+150°C
- With humidity, range: 20~98%RH

Temperature humidity test equipment With high precision perfect external design, external with double sides cold rolled plate electrostatic powder coated material, internal with SUS#304 high temperature resistant stainless steel. Insulation material adopt fire resistant high strength PU polyurethane foaming thermal insulating material. More than 20% energy saving is achieved & thanks to the introducing of German advanced refrigerator control technology. Control system and control circuit components are introduced with famous brand .

Parameter:

Model	TH-408(A~F)	TH-800(A~F)	TH-1000(A~F)
Internal Dimension WxHxD(mm)	600x850x800	1000x1000x800	1000x1000x1000
External Dimension WxHxD(mm)	1200x1950x1350	1600x2000x1450	1600x2100x1450
Temperature Range	Low Temperature (A:25°C B:0°C C:-20°C D:-40°C E:-60°C F:-70°C) High Temperature 150°C		
Humidity Range	20%~98%R.H.(10%-98% R.H. / 5%-98% R.H ,is optional , need Dehumidifier)		
Control Accuracy of Temperature and Humidity	±0.5°C ; ±2.5% R.H.		
Temperature Rising/ Falling Velocity	Temperature rising approx. 0.1~3.0°C/min ; temperature falling approx. 0.1~1.0°C/min; (Falling Min.1.5°C/min is optional)		
Optional Accessories	Inner door with operation hole , Recorder, Water Purifier, Dehumidifier		
Power	AC380V 3 phase 5 lines , 50/60HZ		



® AI SI LI (CHINA) TEST EQUIPMENT CO., LTD


Tel.:0086-769-23164266

Fax:0086-769-22851784

E-mail: sales8@aslitesting.com

Company Add.:Building C,JinHui Industrial Park, LiXin town,East City district 523125,DongGuan City,China

Pictures



® AI SI Li (CHINA) TEST EQUIPMENT CO., LTD

Tel.:0086-769-23164266

Fax:0086-769-22851784

E-mail: sales8@aslitesting.com

Company Add.:Building C,JinHui Industrial Park, LiXin town,East City district 523125,DongGuan City,China