

加速度機械衝擊試驗台 Acceleration Mechanical Shock Tester

機械衝擊試驗台
 Mechanical Shock Tester



技術參數 Technical Parameters:

型號 Model	SS-5	SS-10	SS-25	SS-50	SS-100	SS-200	SS-400
最大負荷 (Kg) Max. Load Capacity (Kg)	5	10	25	50	100	200	400
桌面尺寸WxD(mm) Bench Dimension WxD(mm)	120×120	200×200	350×350	450×450	650×650	750×750	850×850
衝擊峰值加 速度(m/s) Acceleration of shock peak value (m/s)	半正弦波 Half Sine Wave	150~15000	150~15000	150~15000	150~6000	150~6000	150~1500
	梯形波 Trapezoid Wave	300~1000	300~1000	300~1000	300~1000	300~1000	300~500
	後峰鋸齒波 Sawtooth Wave	150~1000	150~1000	150~1000	150~1000	150~1000	150~500
脈衝持續時 間(ms) Pulse width (ms)	半正弦波 Half Sine Wave	0.5~18	0.6~18	0.8~25	1.5~30	1.5~30	6~30
	梯形波 Trapezoid Wave	6~12	6~12	6~18	6~12	6~12	6~12
	後峰鋸齒波 Sawtooth Wave	6~18	6~18	6~18	6~18	6~18	6~18
驅動方式 / Drive Mode	機械驅動 / Mechanical drive				液壓驅動 / Hydraulic drive		
外形尺寸WxHxD(mm) External Dimension WxHxD (mm)	800x2200x900	800x2200x900	850x2250x950	1000x2600x1300	1100x2700x1400	1300x2700x1600	1300x2700x1650
重量 (Kg) / WEIGHT (Kg)	600	700	900	2600	3300	4000	4500
液壓油 / Hydraulic Oil	46號液壓油 No #46 hydraulic oil						
電源 / Power	AC380V ; 3φ 5線 ; 50/60HZ			AC380V ; 3φ 5 lines ; 50/60HZ			